

## CONTACTOS:

-  990-952-267 / 955-792-211
-  [cvalverde@soluplasticperu.com](mailto:cvalverde@soluplasticperu.com)
-  <https://www.soluplasticperu.com>
-  Calle 50 Mz A2 Lt 18 San antonio de Carapongo Lurigancho

HDPE - PVC E.I.R.L // RUC - 20606320265

# SOLUPLASTIC



"SOLUCIONES DE CONFIANZA CALIDAD GARANTIZADA"

## TUBERIA HDPE

### ESPECIFICACIÓN TÉCNICA SEGÚN NORMA ISO 4427, PE-80/PE 100

TRAMO 6 - 9 - 12 MTS										ROLLO X 100 MTS									
SDR 6			SDR 7.4			SDR 9			SDR 11			SDR 13.6			SDR 17				
PE 80	PN 25(362.6 PSI)			PN 20 (290 PSI)			PN 16 (232 PSI)			PN 12.5 (181 PSI)			PN 10 (145 PSI)			PN 8 (116 PSI)			
PE 100				PN 25(362.6 PSI)			PN 20 (290 PSI)			PN 16 (232 PSI)			PN 12.5 (181 PSI)			PN 10 (145 PSI)			
Diámetro Nominal	Diam int. mm	Espesor (mm)	Peso (Kg / mt)	Diam int. mm	Espesor (mm)	Peso (Kg / mt)	Diam int. mm	Espesor (mm)	Peso (Kg / mt)	Diam int. mm	Espesor (mm)	Peso (Kg / mt)	Diam int. mm	Espesor (mm)	Peso (Kg / mt)	Diam int. mm	Espesor (mm)	Peso (Kg / mt)	
16	9.2	3	0.122	10.6	2.3	0.099	11.4	2	0.089		-	-		-	-				
20	12.2	3.4	0.176	13.2	3	0.160	14.6	2.3	0.129	15.4	2	0.114		-	-				
25	15.4	4.2	0.272	17	3.5	0.235	18.2	3	0.207	19.6	2.3	0.165	20.4	2	0.150				
32	19.8	5.4	0.446	22	4.4	0.379	23.8	3.6	0.320	25.2	3	0.274	26.4	2.4	0.230	27.4	2	0.191	
40	25	6.7	0.691	27.6	5.5	0.590	29.8	4.5	0.499	31.6	3.7	0.421	33	3	0.357	34.4	2.4	0.286	
50	31.4	8.3	1.071	34.6	6.9	0.923	37.4	5.6	0.774	39.6	4.6	0.653	41.6	3.7	0.548	43.2	3	0.445	
63	39.6	10.5	1.703	43.8	8.6	1.450	47	7.1	1.233	50	5.8	1.034	52.4	4.7	0.873	54.4	3.8	0.706	
75	47.2	12.5	2.412	52	10.3	2.063	56.2	8.4	1.736	59.8	6.8	1.443	62.4	5.6	1.234	64.8	4.5	0.994	
90	56.6	15	3.470	62.6	12.3	2.955	67.4	10.1	2.501	71.6	8.2	2.084	75	6.7	1.768	77.8	5.4	1.427	
110	69.4	18.3	5.173	76.4	15.1	4.428	82.6	12.3	3.721	87.8	10	3.103	91.8	8.1	2.609	95.2	6.6	2.128	